


[Back to search form](#)

Search result

| | |
|--|---|
| QUERY | |
| Search done on | 7.4.2009 (16:28h) |
| Search ID | 10536455 |
| Database | Metallic compounds |
| Composition (Dimension: weight-%, Limit for optional components: 0) | C: 0.10-0.15* NB: 0.04-0.10* B: 0.001-0.005* MO: 0.15-0.35* MN: 1.3-2.0* SI: 0.15-1.30* AL: 0.01-0.08* N: 0-0.015* TI: 0.0001-10* FE: BALANCE |
| Sorted according to | Date of publication descending |

Compositions

Hits 389

| 1 - DEUTSCHES PATENT- UND MARKENAMT DPMA - 7.4.2009 (16:28h) | | |
|--|--|-----------------------|
| Field | Content | |
| Publication | EP1816225 A1 | 08.08.2007 |
| Priority | JP2004342024 | 26.11.2004 |
| Application | EP0109200505781981 | |
| Applicant | JFE Steel Corp. | |
| Inventor | Ishiguro, Yasuhide; Kawabata, Yoshikazu; Sakata, Kei und Miterfinder | |
| Title | Steel pipe having excellent electromagnetic properties and process for producing the same | |
| Info | | |
| IPC | C22C038/00 | |
| Composition nr. | 1 | Composite component - |
| Composition | [weight-%]: C: 0-0,5 * SI: 0-0,45 * MN: 0,1-1,4 * P: 0-0,025 * S: 0-0,01 * AL: 0,01-0,06 * N: 0-0,005 * TI: 0-0,05 + NB: 0-0,05 + B: 0-0,005 * CR: 0-15 + NI: 0-0,5 + MO: 0-0,3 * CA: 0-0,005 + REM: 0-0,05 * FE: REST | |
| Keywords | (english) | (german) |
| | HEAT-TREATMENT | WÄRMEBEHANDLUNG |
| | MAGNETIZABLE | MAGNETISIERBAR |
| | PLASTIC | PLASTISCH |
| | TEXTURE | TEXTUR |
| | USE | VERWENDUNG |

2 - DEUTSCHES PATENT- UND MARKENAMT DPMA - 7.4.2009 (16:30h)